

SYSTEM M STANDARD COMPONENTS :
ceiling plate, top pivot, closer body, floor plate

Big pivot doors have been around for at least five-thousand years, and hydraulic pivot door closers for the last century. When FritsJurgens introduced the System M a few years ago, it fundamentally changed how pivot doors were seen by designers and builders.

Their new technology eliminated the hassle and expense that came with installing traditional closers into a big cavity in the floor. FritsJurgens had engineered a heavy-duty adjustable pivot and closer mortised entirely in the door, a simple innovation that saved time and money for all involved, freeing the architect to imagine larger and heavier pivot doors.

Now, continuing the technological development comes System M+, delivering increased control and capacity for doors with FritsJurgens inside, and moving the development of pivot closers into the future.



M32



M32+



M42+

SYSTEM M (the original)

SYSTEM M+ (two new models that continue the revolution)

It's all in the door.

- Double-acting pivot+closer for any door.
- Minimum pivot offset : 3-9/16" (91mm)
- Hold positions at $\pm 90^\circ$ and 0°
- Closing from $\pm 90^\circ$ and $\pm 125^\circ$
- Adjustable Damper Control for doors up to **440 lbs.**
- Back-check providing resistance upon opening to protect doors and walls.
- Minimum door thickness : 1-9/16" (40mm)
Unlimited door height.
- Class 5 Corrosion Resistance and Maintenance-free.
- ADA-compliant models are available.

+ Latching

- **M32+** | The same closer body dimensions, hold positions, and construction as the System M, but for doors up to **770 lbs.**


Three Speed Adjustments :

- Adjustable Damper/Backcheck Control
- + Adjustable 30° Speed Control: controls the last part of the closing.
- + Adjustable Latching Control: controls acceleration prior to closing.


+ Capacity

- **M42+** | All the same functionality and adjustability as the System M32+


- + increased capacity for doors up to **1100 lbs.**
- Larger closer body than the M32+
M32/M32+ : 3.92" H x 11.60" W x 1.26"D
M42+ : 4.44" H x 12.13" W x 1.57"D
- Minimum door thickness : 2" (50mm)



DAMPER CONTROL



30° SPEED CONTROL



LATCH CONTROL

